

Vibrostop TSPP



Sede acciaio
Steel seat

CARATTERISTICHE

Features

- Possibilità di carico da 50 daN a 1500 daN per antivibrante
- Ingombro in altezza ridotto.
- Cappuccio in alluminio a protezione dell'elastomero.

- *Loading up between 50 daN and 1500 daN each A.V. Mountings.*
- *Low height.*
- *Aluminium cap to shelter the elastomer*

MATERIALI

Materials

- Componenti in gomma: elastomero Vibrostop.
- Componenti in metallo: lega di alluminio

- *Rubber components: Vibrostop elastomer.*
- *Metal components: aluminium alloy*

APPLICAZIONI

Applications

- Presse - Magli - Cesoie - Macchine utensili
- Torri evaporative - Gruppi di condizionamento
- Pavimenti flottanti - Pianoforti.


- *Presses - Hammers - Shears - Machine tool - Cooling towers - Air conditioning units - Floating floor - Pianos.*

INSTALLAZIONE

Installation

- Appoggio oppure fissaggio (opzionale) tra macchina e antivibrante.
- Semplice appoggio a pavimento.

- *Leaning or fixing (optional) between machine and A.V. mounting.*
- *Simple leaning to the floor.*







PORTATA LOAD				DIMENSIONI DIMENSIONS	
AS MESCOLA ALTA SESIBILITA' <i>HIGH SENSITIVITY</i> [45° Sh]		N MESCOLA NORMALE <i>NORMAL</i> [60° Sh]		A [mm]	B [mm]
TIPO <i>Type</i>	CARICO <i>Load</i> [daN]	TIPO <i>Type</i>	CARICO <i>Load</i> [daN]		

Dimensioni indicative

Dimensions for reference only

Diagrammi di carico

Load diagrams



Curve caratteristiche indicative

Performance characteristics for reference only